



LOCOMOTIVE POWER GEAR OIL 75W-85 GL-5

PRODUCT DESCRIPTION:

LOCOMOTIVE 75W-85 GL-5 is a superior transmission fluid designed for heavy duty driveline components requiring special low temperature fluidity. The product offers best-in-class protection against extreme pressure and wear due to exceptional stability in high as well as low temperatures. This results in optimized lubrication of hypoid and non-hypoid axles.

APPLICATION:

LOCOMOTIVE 75W-85 GL-5 is designed for heavy duty drive-line components such as rear-axes, final drives and selected manual transmissions, requiring special low temperature fluidity to reduce fuel consumption or facilitate gear shifting.

FEATURES & BENEFITS:

- Reduced cold viscosity for excellent fuel efficiency.
- Economy grade for modern passenger car manual gearboxes according to the manufacturer's specification.
- Very good protection against wear and corrosion.
- High temperature and oxidation stability due to fully synthetic base oils and special additives.
- Extremely stable to shear stress - 'Stay-in-grade.'
- Stable lubricating film, even with very hot oil and under very high loads. As a result, reduced wear and lower gearbox noise.
- Excellent cold viscosity ensures improved shifting ability, fast lubrication and low 'cold wear'.

PERFORMANCE LEVELS: Meets and Exceeds:

- API GL-5
- MIL-L-2105D

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			75W-85
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	71
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	11.6
Viscosity Index	ASTM D2270	-	158
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.874
Flash Point	ASTM D92	°C	224
Pour Point	ASTM D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website Locomotive.com